



हमसे कोई
छुप नहीं सकता

PROSONIC
Securing People

PRO- IP-3000



**2MP Smart IR Bullet IP
Long-focus AF Camera**

Features

- 1/2.8" Sony STARVIS CMOS sensor
- FHD resolution 1920 x 1080P
- Low illumination 0.001Lux
- Day/Night, AWB/MWB,BLC, HLC, 2D/3D-DNR,Shutter, IR-CUT
- D-WDR, Mirror, Defogging
- Multiply Style OSD Overlay,Motion Detection, Privacy Mask
- RTSP and Onvif 17.06 compatible with many third-party NVR
- H.264/H.265 dual-stream media server
- Easy-to-use P2P Cloud service
- Support user authentication, video data encryption
- Support Alarm Snapshot to Email and FTP
- Multiply WEB browser IE,Firefox 32bit ESR, PC Client, Mobile APP remote access
- Lightning protection
- Strong water-proof housing, IP66
- 4 pcs Hi-power Array IR Leds, IR distance 70 - 80 meters
- HD 5 – 50 mm AF lens

Camera	Specification
Image sensor	1/2.8" Sony STARVIS CMOS
Effective Pixels	2 megapixels
Electronic Shutter	AUTO
Min. Illumination	0.001Lux@F1.2(AGC ON)
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto
AGC/BLC/HLC	Support
DNR	2D/3D DNR
Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Flip
Encode	Specification
Video Standard	H.265/H.264
Video Resolution	Main Stream:30/25fps@1080P/720P Sub Stream: VGA(640x480)/360P/QVGA@25fps, etc.
Video Bitrates	Free client software
OSD Overlay	12VDC / 2A
IR Led	Specification
IR Led	4 pcs high power array IR Led
IR Distance	70-80 M
Lens	Specification
Focal length	5 -50 mm AF lens
Zoom	10x optical zoom
Network services	Specification
Protocol	HTTP/RTSP/FTP/NFS/SMTP/DHCP/NTP, etc.
P2P	Yes
Web	IE , Firefox 32bit esr
Media	CMS, Android, IOS
ONVIF	17.06 compatible
General	Specification
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC ± 10%

Power Consumption	< 10 W
Operating Temp.	-30°C-(+60)°C, 10%-90%RH

