



हमसे कोई
छुप नहीं सकता

PROSONIC
Securing People

PRO-POE-208

1-8 Port: 250m Distance Gigabit PoE Switch

Main Feature:

- 8*10/100/1000Mbps PoE port, 2*10/100/1000Mbps uplink port;
- Support IEEE802.3af/at;
- Support restrain network storm, VLAN function;
- Max Transmission distance up to 250m with PoE Power;
- Built-in power supply;
- Maximum power of single PoE port: 10*30w;
- Maximum PoE power: 300w;
- Adopts store-and-forward architecture;
- Fanless, natural cooling, small, compact and quiet design, suitable for desktop or wall;
- Support lightning protection 6000V;



Feature	Specification
Power Adapter Voltage	AC 110V-240V
Consumption	120W(52V 2.3A)
PoE Ethernet Port	1-8 port:10/100/1000Mbps
Ethernet Port	Uplink port:10/100/1000Mbps
Transmission Distance	1000Mbps:0-100m/100Mbps;0-250m/Uplink Port:0-1000m
Transmission Medium	Cat5/5e/6 standard network cable
Network Standard	IEEE802.3/802.3u,IEEE802.3x,IEEE802.3ab
Switching Capacity	5.6Gbps
Packet Buffer Memory	1Mbits
Throughput	4.1664Mbps
MAC Table	2K
Packet Forwarding rate	10Mbps:14880pps/port, 100Mbps:148800pps/port, 1000Mbps: 1488000pps/port
PoE Standard	IEEE802.3af/at
PoE Power Supply	End-Span(1/2 + ; 3/6 -)
PoE Power	af=15.4w,at=30w for each por
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and back pressure for Half-duplex mode
LED Indicator	LINK/ACT 100Mbps: PoE Status Indicator, Power Indicator, Extender
Working temperature	0℃~50℃
Relative Humidity	20-95%
Storage temperature	-20℃~70℃
Dimension(L*W*H)	202mm*140mm*45mm,
Color & Weight	Black 1.05Kg

